



077650 SERIES • ANSI GRADE 3

A commercial quality deadbolt that provides a positive deterrent to forced entry.

- Fixed backset 1" (25mm) deadbolt with hardened steel core exceeds ANSI Grade 2 Security against kick-in and saw attacks.
- 2 dia taped cylinder guard and metal insert, turns free with any removal attempt.
- High precision pick-resistant solid metal tumbler plug.
 5 or 6 pin available. Brass key nickel plated. "C", Kwikset keyway available.
- Drive in deadbolt Designed to be installed on metal door conveniently. Only one hole is needed on door edge.
- ADA Ergonomic thumb turn.
- Brass bolt nickel plated
- Zinc mounting plate.
- Sturdy, steel latch case.
- Adapter for 2-1/8" hole.
- Finishes Available:
 - **PB** Polished Brass
 - SB Satin Brass
 - **AB** Antique Brass
 - AC Antique Copper
 - SN Satin Nickel
 - SC Satin Chrome
 - CR Polished Chrome
 - ORB Oil Rubbed Bronze
 - TB Black Nickel
 - AN Antique Nickel
 - PVD Lifetime finish



| r | , |
|-----------------|--|
| Door Prep: | Cross bore 2-1/8", Edge bore 1" Latch face 1"x2-1/4". |
| Backset: | 2-3/4" standard, 2-3/8" optional. |
| Door Thickness: | Adjustable 1-3/8" 2". |
| Cylinder: | 5-Pin or 6-Pin removable core. Schlage "C " keyway or Kwikset and other options available. |
| Face plates: | 1"x2-1/4" square corner standard. Round corner and other options available. |
| Strikes: | 2-3/4" square corner standard. Round corner and other options available. |
| Bolt: | 1" throw. Nickel plated. |
| ANSI/BHMA: | A156.5 Grade 3. |

International Door Closers, Inc.

COPYRIGHT 2018 INTERNATIONAL DOOR CLOSERS, INC



Inside Rose Assembly

SINGLE CYLINDER 077651 SN



