

VL LISTED ELECTROMAGNETIC LOCKS WAGLOCKS ULTIMATE PROTECTION

FEATURES

- Lock status sensor (bond sensor) and visual LED on 600 and 1200 lb models
- Includes adjustable relock time delay (0 90 secs)
- Field selectable 12/24V DC
- Installation hardware included for typical applications
- Convenient plug-in wire terminals
- Available for single doors and double doors without center mullion



IDC Maglocks offer the ultimate protection for most access control applications.

EASY INSTALLATION MULTIPLE MODELS



10MAGLOCK1UL 1200LB – SINGLE



10MAGLOCK3UL 600LB – SINGLE



10MAGLOCK5UL 1200LB – DOUBLE



10MAGLOCK6UL 600LB – DOUBLE



10LZBRMAG1UL (1) 'L' and (1) 'Z'



10LZBRMAG3UL (1) 'L' and (1) 'Z' use with 10MAGLOCK3UL



10UBRACKETUL U-Bracket – Glass Doors



MAG5LZUL MAG6LZUL (2) 'L' and (2) 'Z'



10FILLER12UL 10FILLER34UL FILLER BAR



Vertical Spacer Bars



Armature Housing

International Door Closers, Inc.

COPYRIGHT 2018 INTERNATIONAL DOOR CLOSERS, INC

West: 800-544-4422 • East: 800-225-6737

www.intldoorclosers.com

TECHNICAL SPECIFICATIONS

10MAGLOCK3UL Single 10MAGLOCK6UL Double

HOLDING FORCE

INPUT VOLTAGE 600 lbs 12 or 24V DC

> Note: This product is recommended to be used with a UL-Listed Power Supply

CURRENT DRAW

Single 0.50A @ 12V DC 0.25A @ 24V DC

1.00A @ 12 VDC 0.50A @ 24V DC

DIMENSIONS Single

9.84" × 1.85" × 1.02" $(250 \text{mm} \times 47 \text{mm} \times 26 \text{mm})$

19.76" × 1.85" × 1.02" $(502mm \times 47mm \times 26mm)$ HOLD TIMER 0-90 sec

HOLD TIMER

0-90 sec

10MAGLOCK1UL Single 10MAGLOCK5UL Double

HOLDING FORCE

1200 lbs

Note: This product is recommended to be used with a UL-Listed **Power Supply**

INPUT VOLTAGE

12 or 24V DC

CURRENT DRAW

Single 0.50A @ 12V DC 0.25A @ 24V DC

Dual 1.03A @ 12V DC 0.52A @ 24V DC

DIMENSIONS

Single 10.47" × 2.91" × 1.58" (266mm × 74mm × 40mm)

Dual

20.94" × 2.91" × 1.58" (532mm × 74mm × 40mm)

MAGLOCK APPLICATIONS




Install IDC Maglocks in security applications including: portals in hotels, retail outlets or where egress control is needed

Maglocks

Armature Plate

► IDC Maglocks, when combined with IDC's other security products, are designed to ensure ultimate security in clean room, airlock, and also mantrap applications



 Clean Room / Airlock Application

RELATED PRODUCTS



R2F-100 UL / ULC Listed, Active Infrared, Request To Exit Detector designed for access control applications

Swinging Door Application



Weather Resistant Maglocks Increased protection on more heavy duty doors and gates



Cylindrical Strikes UL / ULC Listed, low profile, all-in-one, universal electric strike



www.intldoorclosers.com

West: 800-544-4422 • East: 800-225-6737

Rim/Fxit Strikes UL / ULC Listed, surface mount electric strike